

# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations  
Revision Date: 11/13/2024 Date of Issue: 11/13/2024

Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Ultimate 6K Fuel Enhancer

**Product Part #:** UF601

#### 1.2. Intended Use of the Product

**Use of the Substance/Mixture:** Automotive.

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Company

Ultimate Automotive Products, Inc.

7696 SW Jack James Drive

Stuart, FL 34997

772-600-5138

[www.ultimateautomotiveproducts.com](http://www.ultimateautomotiveproducts.com)

#### 1.4. Emergency Telephone Number

**Emergency Number** : 813-248-0585 ChemTel

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### GHS-US Classification

Flam. Liq. 2 H225

Acute Tox. 4 (Oral) H302

Acute Tox. 3 (Dermal) H311

Skin Irrit. 2 H315

Eye Dam. 1 H318

Skin Sens. 1 H317

Muta. 1B H340

Carc. 1B H350

Repr. 1B H360

STOT SE 3 H336

STOT SE 3 H335

Asp. Tox. 1 H304

Aquatic Acute 2 H401

Aquatic Chronic 2 H411

Full text of hazard classes and H-statements : see Section 16.

#### 2.2. Label Elements

##### GHS-US Labeling

##### Hazard Pictograms (GHS-US)



##### Signal Word (GHS-US)

: Danger

##### Hazard Statements (GHS-US)

: H225 - Highly flammable liquid and vapor.  
H302 - Harmful if swallowed.  
H304 - May be fatal if swallowed and enters airways.  
H311 - Toxic in contact with skin.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H340 - May cause genetic defects.  
H350 - May cause cancer.  
H360 - May damage fertility or the unborn child.  
H401 - Toxic to aquatic life.

# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Precautionary Statements (GHS-US)

H411 - Toxic to aquatic life with long lasting effects.  
: P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from extremely high or low temperatures, ignition sources, and incompatible materials. - No smoking.  
P240 - Ground/Bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P261 - Avoid breathing vapors, mist, or spray.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P301+P310 - If swallowed: Immediately call a poison center or doctor.  
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321 - Specific treatment (see Section 4 on this SDS).  
P322 - Specific treatment (see supplemental first aid instruction on this label).  
P330 - Rinse mouth.  
P331 - Do NOT induce vomiting.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media (see Section 5) to extinguish.  
P391 - Collect spillage.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.  
P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
P308+310+313 - If exposed or concerned: Get medical advice/attention. Immediately call a poison center or doctor.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixture

| Name   | Product Identifier   | %       | GHS-US classification   |
|--|----------------------|---------|---|
| Solvent naphtha, petroleum, medium aliphatic | (CAS-No.) 64742-88-7 | 29.6-37 | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 2, H411 |

# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |                       |            |   |
|--|-----------------------|------------|---|
| 2-Butoxyethanol  | (CAS-No.) 111-76-2    | 22.2-29.6  | Flam. Liq. 4, H227<br>Acute Tox. 4 (Oral), H302<br>Acute Tox. 3 (Dermal), H311<br>Acute Tox. 3<br>(Inhalation:vapor), H331<br>Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319<br>STOT SE 3, H336   |
| Xylenes (o-, m-, p- isomers)   | (CAS-No.) 1330-20-7   | >20        | Flam. Liq. 3, H226<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4<br>(Inhalation:vapor), H332<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401  |
| Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-, branched | (CAS-No.) 127087-87-0 | 3.7 - 11.1 | Acute Tox. 4 (Oral), H302<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Aquatic Acute 3, H402<br>Aquatic Chronic 2, H411  |
| Benzene, 1,2,4-trimethyl-  | (CAS-No.) 95-63-6     | 0.5 - 3.7  | Flam. Liq. 3, H226<br>Acute Tox. 4<br>(Inhalation:vapor), H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 2, H411  |
| Acetone  | (CAS-No.) 67-64-1     | 0.5 - 3.7  | Flam. Liq. 2, H225<br>Eye Irrit. 2A, H319<br>STOT SE 3, H336  |
| Turpentine, oil  | (CAS-No.) 8006-64-2   | 0.5-1      | Flam. Liq. 2, H225<br>Acute Tox. 4 (Oral), H302<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4<br>(Inhalation:vapor), H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2B, H320<br>Skin Sens. 1, H317<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 2, H411 |
| Solvent naphtha, petroleum, light aliphatic                                  | (CAS-No.) 64742-89-8  | 0.5 - 0.6  | Flam. Liq. 1, H224<br>Skin Irrit. 2, H315<br>Muta. 1B, H340<br>Carc. 1B, H350<br>Repr. 2, H361<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 2, H411  |

# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                   |                       |            |   |
|-----------------------------------|-----------------------|------------|---|
| Toluene                           | (CAS-No.) 108-88-3    | 0.1-.5     | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>Repr. 2, H361<br>STOT SE 3, H336<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 3, H412   |
| Proprietary Component 1           | (CAS-No.) Proprietary | 1-5        | Not classified (polymers)   |
| Polyetheramine (PEA)<br>Additives | (CAS-No.) Proprietary | 0.1-.5     | Flam. Liq. 3, H226<br>Carc. 2, H351<br>STOT SE 3, H336<br>STOT SE 3, H335<br>Asp. Tox. 1, H304  |
| Ethylbenzene                      | (CAS-No.) 100-41-4    | 0.1 - 0.15 | Flam. Liq. 2, H225<br>Acute Tox. 4<br>(Inhalation:vapor), H332<br>Carc. 2, H351<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 2, H411 |
| 1-Methyl-2-pyrrolidone            | (CAS-No.) 872-50-4    | >0.1       | Flam. Liq. 4, H227<br>Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319<br>Repr. 1B, H360<br>STOT SE 3, H335   |

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

Full text of H-phrases: see Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**First-aid Measures After Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Get immediate medical advice/attention.

**First-aid Measures After Eye Contact:** Get immediate medical advice/attention. Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**First-aid Measures After Ingestion:** Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**Symptoms/Injuries:** Causes skin irritation. May cause respiratory irritation. May cause drowsiness and dizziness. Harmful if swallowed. Toxic in contact with skin. Causes serious eye damage. Skin sensitization. May cause genetic defects. May cause cancer. May damage fertility. May damage the unborn child. May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** Irritation of the respiratory tract and the other mucous membranes. High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

**Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis. This material is toxic in small amounts through skin contact, and can cause adverse health effects or death. This material may be absorbed through the skin and eyes. May cause an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva.

**Symptoms/Injuries After Ingestion:** This material is harmful orally and can cause adverse health effects or death in significant amounts. Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** May cause genetic defects. May cause cancer. May damage fertility or the unborn child.

# Ultimate 6K Fuel Enhancer

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>). Water may be ineffective but water should be used to keep fire-exposed container cool.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. A heavy water stream may spread burning liquid.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Highly flammable liquid and vapor.

**Explosion Hazard:** May form flammable or explosive vapor-air mixture.

**Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Irritating fumes, smoke, oxides of carbon and hydrocarbons.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges. Do not breathe vapor, mist or spray.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area. Eliminate ignition sources.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable. Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid contact with eyes, skin and clothing. Handle empty containers with care because they may still present a hazard. Do not get in eyes, on skin, or on clothing.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

**Storage Conditions:** Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place. Store locked up.

# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

### 7.3. Specific End Use(s)

Automotive.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in Section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

| 2-Butoxyethanol (111-76-2)               |                                      |   |
|--|--------------------------------------|---|
| USA ACGIH                                | ACGIH TWA (ppm)                      | 20 ppm  |
| USA ACGIH                                | ACGIH chemical category              | Confirmed Animal Carcinogen with Unknown Relevance to Humans  |
| USA ACGIH                                | Biological Exposure Indices (BEI)    | 200 mg/g Kreatinin Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift                           |
| USA NIOSH                                | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 24 mg/m <sup>3</sup>  |
| USA NIOSH                                | NIOSH REL (TWA) (ppm)                | 5 ppm   |
| USA IDLH                                 | US IDLH (ppm)                        | 700 ppm   |
| USA OSHA                                 | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 240 mg/m <sup>3</sup>   |
| USA OSHA                                 | OSHA PEL (TWA) (ppm)                 | 50 ppm  |
| USA OSHA                                 | Limit value category (OSHA)          | prevent or reduce skin absorption   |
| Acetone (67-64-1)                        |                                      |   |
| USA ACGIH                                | ACGIH TWA (ppm)                      | 250 ppm   |
| USA ACGIH                                | ACGIH STEL (ppm)                     | 500 ppm   |
| USA ACGIH                                | ACGIH chemical category              | Not Classifiable as a Human Carcinogen  |
| USA ACGIH                                | Biological Exposure Indices (BEI)    | 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift (nonspecific)  |
| USA NIOSH                                | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 590 mg/m <sup>3</sup>   |
| USA NIOSH                                | NIOSH REL (TWA) (ppm)                | 250 ppm   |
| USA IDLH                                 | US IDLH (ppm)                        | 2500 ppm (10% LEL)  |
| USA OSHA                                 | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 2400 mg/m <sup>3</sup>  |
| USA OSHA                                 | OSHA PEL (TWA) (ppm)                 | 1000 ppm  |
| Benzene, 1,2,4-trimethyl- (95-63-6)      |                                      |   |
| USA NIOSH                                | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 125 mg/m <sup>3</sup>   |
| USA NIOSH                                | NIOSH REL (TWA) (ppm)                | 25 ppm  |
| Xylenes (o-, m-, p- isomers) (1330-20-7) |                                      |   |
| USA ACGIH                                | ACGIH TWA (ppm)                      | 100 ppm   |
| USA ACGIH                                | ACGIH STEL (ppm)                     | 150 ppm   |
| USA ACGIH                                | ACGIH chemical category              | Not Classifiable as a Human Carcinogen  |
| USA ACGIH                                | Biological Exposure Indices (BEI)    | 1.5 g/g Kreatinin Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift   |
| USA OSHA                                 | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 435 mg/m <sup>3</sup>   |
| USA OSHA                                 | OSHA PEL (TWA) (ppm)                 | 100 ppm   |
| Turpentine, oil (8006-64-2)              |                                      |   |
| USA ACGIH                                | ACGIH TWA (ppm)                      | 20 ppm  |
| USA ACGIH                                | ACGIH chemical category              | dermal sensitizer, Not Classifiable as a Human Carcinogen   |
| USA NIOSH                                | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 560 mg/m <sup>3</sup>   |
| USA NIOSH                                | NIOSH REL (TWA) (ppm)                | 100 ppm   |
| USA IDLH                                 | US IDLH (ppm)                        | 800 ppm   |
| USA OSHA                                 | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 560 mg/m <sup>3</sup>   |
| USA OSHA                                 | OSHA PEL (TWA) (ppm)                 | 100 ppm   |
| Ethylbenzene (100-41-4)                  |                                      |   |
| USA ACGIH                                | ACGIH TWA (ppm)                      | 20 ppm  |
| USA ACGIH                                | ACGIH chemical category              | Confirmed Animal Carcinogen with Unknown Relevance to Humans  |
| USA ACGIH                                | Biological Exposure Indices (BEI)    | 0.15 g/g Kreatinin Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: end of shift (nonspecific) |

# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |  |  |
|--|--|--|
| <b>USA NIOSH</b>                         | NIOSH REL (TWA) (mg/m <sup>3</sup> )   | 435 mg/m <sup>3</sup>  |
| <b>USA NIOSH</b>                         | NIOSH REL (TWA) (ppm)  | 100 ppm  |
| <b>USA NIOSH</b>                         | NIOSH REL (STEL) (mg/m <sup>3</sup> )  | 545 mg/m <sup>3</sup>  |
| <b>USA NIOSH</b>                         | NIOSH REL (STEL) (ppm)   | 125 ppm  |
| <b>USA IDLH</b>                          | US IDLH (ppm)  | 800 ppm (10% LEL)  |
| <b>USA OSHA</b>                          | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 435 mg/m <sup>3</sup>  |
| <b>USA OSHA</b>                          | OSHA PEL (TWA) (ppm)   | 100 ppm  |
| <b>1-Methyl-2-pyrrolidone (872-50-4)</b> |  |  |
| <b>USA ACGIH</b>                         | Biological Exposure Indices (BEI)  | 100 mg/l Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone - Medium: urine - Sampling time: end of shift   |
| <b>USA AIHA</b>                          | WEEL TWA (ppm)   | 10 ppm   |
| <b>USA AIHA</b>                          | AIHA chemical category   | skin notation  |
| <b>2-Butoxyethanol (111-76-2)</b>        |  |  |
| <b>USA ACGIH</b>                         | ACGIH TWA (ppm)  | 20 ppm   |
| <b>USA ACGIH</b>                         | ACGIH chemical category  | Confirmed Animal Carcinogen with Unknown Relevance to Humans   |
| <b>USA ACGIH</b>                         | Biological Exposure Indices (BEI)  | 200 mg/g Kreatinin Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift  |
| <b>USA NIOSH</b>                         | NIOSH REL (TWA) (mg/m <sup>3</sup> )   | 24 mg/m <sup>3</sup>   |
| <b>USA NIOSH</b>                         | NIOSH REL (TWA) (ppm)  | 5 ppm  |
| <b>USA IDLH</b>                          | US IDLH (ppm)  | 700 ppm  |
| <b>USA OSHA</b>                          | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 240 mg/m <sup>3</sup>  |
| <b>USA OSHA</b>                          | OSHA PEL (TWA) (ppm)   | 50 ppm   |
| <b>USA OSHA</b>                          | Limit value category (OSHA)  | prevent or reduce skin absorption  |
| <b>Toluene (108-88-3)</b>                |  |  |
| <b>USA ACGIH</b>                         | ACGIH TWA (ppm)  | 20 ppm   |
| <b>USA ACGIH</b>                         | ACGIH chemical category  | Not Classifiable as a Human Carcinogen   |
| <b>USA ACGIH</b>                         | Biological Exposure Indices (BEI)  | 0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek<br>0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift<br>0.3 mg/g Kreatinin Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background) |
| <b>USA NIOSH</b>                         | NIOSH REL (TWA) (mg/m <sup>3</sup> )   | 375 mg/m <sup>3</sup>  |
| <b>USA NIOSH</b>                         | NIOSH REL (TWA) (ppm)  | 100 ppm  |
| <b>USA NIOSH</b>                         | NIOSH REL (STEL) (mg/m <sup>3</sup> )  | 560 mg/m <sup>3</sup>  |
| <b>USA NIOSH</b>                         | NIOSH REL (STEL) (ppm)   | 150 ppm  |
| <b>USA IDLH</b>                          | US IDLH (ppm)  | 500 ppm  |
| <b>USA OSHA</b>                          | OSHA PEL (TWA) (ppm)   | 200 ppm  |
| <b>USA OSHA</b>                          | OSHA PEL (Ceiling) (ppm)   | 300 ppm  |
| <b>USA OSHA</b>                          | Acceptable Maximum Peak Above The Acceptable Ceiling Concentration For An 8-Hr Shift | 500 ppm Peak (10 minutes)  |

## 8.2. Exposure Controls

### Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

### Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection. Face shield.



# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |  |
|--|--|
| <b>Materials for Protective Clothing</b> | : Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.  |
| <b>Hand Protection</b>                   | : Wear protective gloves.  |
| <b>Eye and Face Protection</b>           | : Chemical safety goggles.   |
| <b>Skin and Body Protection</b>          | : Wear suitable protective clothing.   |
| <b>Respiratory Protection</b>            | : If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection. |
| <b>Other Information</b>                 | : When using, do not eat, drink or smoke.  |

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

|   |                     |
|---|---------------------|
| <b>Physical State</b>                         | : Liquid            |
| <b>Appearance</b>                             | : clear             |
| <b>Odor</b>                                   | : No data available |
| <b>Odor Threshold</b>                         | : No data available |
| <b>pH</b>                                     | : No data available |
| <b>Evaporation Rate</b>                       | : No data available |
| <b>Melting Point</b>                          | : No data available |
| <b>Freezing Point</b>                         | : No data available |
| <b>Boiling Point</b>                          | : No data available |
| <b>Flash Point</b>                            | : 26°C (78.8°F)     |
| <b>Auto-ignition Temperature</b>              | : No data available |
| <b>Decomposition Temperature</b>              | : No data available |
| <b>Flammability (solid, gas)</b>              | : Not applicable    |
| <b>Vapor Pressure</b>                         | : No data available |
| <b>Relative Vapor Density at 20°C</b>         | : No data available |
| <b>Relative Density</b>                       | : No data available |
| <b>Solubility</b>                             | : No data available |
| <b>Partition Coefficient: N-Octanol/Water</b> | : No data available |
| <b>Viscosity</b>                              | : No data available |

### 9.2. Other Information

No additional information available

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.
- 10.2. Chemical Stability:** Highly flammable liquid and vapor. May form flammable or explosive vapor-air mixture.
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** None expected under normal conditions of use.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects

**Acute Toxicity:** Oral: Harmful if swallowed. Dermal: Toxic in contact with skin.

|  |                            |
|--|----------------------------|
| <b>Ultimate 6K Fuel Enhancer</b>                                 |                            |
| <b>ATE (Oral)</b>  | 1,352.74 mg/kg body weight |
| <b>ATE (Dermal)</b>  | 843.52 mg/kg body weight   |
| <b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b> |                            |
| <b>LD50 Oral Rat</b>   | > 25 ml/kg                 |
| <b>LD50 Dermal Rabbit</b>  | > 3000 mg/kg               |
| <b>LC50 Inhalation Rat</b>                                       | > 13 mg/l/4h               |
| <b>2-Butoxyethanol (111-76-2)</b>                                |                            |
| <b>LD50 Oral Rat</b>   | 470 mg/kg                  |



# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|   |  |
|---|--|
| LD50 Dermal Rabbit  | > 841 mg/kg                              |
| LC50 Inhalation Rat   | 2.2 mg/l/4h                              |
| ATE (Dermal)  | 300.00 mg/kg body weight                 |
| <b>Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-, branched (127087-87-0)</b> |  |
| LD50 Oral Rat   | 1310 mg/kg                               |
| <b>Acetone (67-64-1)</b>  |  |
| LD50 Oral Rat   | 5800 mg/kg                               |
| LD50 Dermal Rabbit  | 15688 mg/kg                              |
| LC50 Inhalation Rat   | 44 g/m <sup>3</sup>                      |
| <b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>  |  |
| LD50 Oral Rat   | 6000 mg/kg                               |
| LD50 Dermal Rabbit  | > 3160 mg/kg                             |
| LC50 Inhalation Rat   | 18 g/m <sup>3</sup> (Exposure time: 4 h) |
| LC50 Inhalation Rat   | 10.8 mg/l/4h                             |
| <b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>   |  |
| LD50 Oral Rat   | > 5000 mg/kg                             |
| LC50 Inhalation Rat   | 27.57 mg/l/4h                            |
| ATE (Dermal)  | 1,100.00 mg/kg body weight               |
| ATE (Vapors)  | 11.00 mg/l/4h                            |
| <b>Turpentine, oil (8006-64-2)</b>  |  |
| LD50 Oral Rat   | 4.6 ml/kg                                |
| LD50 Dermal Rabbit  | > 5010 mg/kg                             |
| LC50 Inhalation Rat   | 12 g/m <sup>3</sup> (Exposure time: 6 h) |
| LC50 Inhalation Rat   | 13.7 mg/l/4h                             |
| ATE (Oral)  | 500.00 mg/kg body weight                 |
| ATE (Dermal)  | 1,100.00 mg/kg body weight               |
| <b>Solvent naphtha, petroleum, light aliphatic (64742-89-8)</b>                                   |  |
| LD50 Oral Rat   | >= 5000 mg/kg                            |
| LD50 Dermal Rabbit  | 3000 mg/kg                               |
| <b>Ethylbenzene (100-41-4)</b>  |  |
| LD50 Oral Rat   | 3500 mg/kg                               |
| LD50 Dermal Rabbit  | 15400 mg/kg                              |
| LC50 Inhalation Rat   | 17.2 mg/l/4h (Exposure time: 4 h)        |
| <b>1-Methyl-2-pyrrolidone (872-50-4)</b>  |  |
| LD50 Oral Rat   | 4150 mg/kg                               |
| LD50 Dermal Rabbit  | > 5000 mg/kg                             |
| LC50 Inhalation Rat   | 5.1 mg/l/4h                              |
| LC50 Inhalation Rat   | 5.1 mg/l/4h                              |
| <b>2-Butoxyethanol (111-76-2)</b>   |  |
| LD50 Oral Rat   | 470 mg/kg                                |
| LD50 Dermal Rabbit  | 435 mg/kg                                |
| LC50 Inhalation Rat   | 2.2 mg/l/4h                              |
| LC50 Inhalation Rat   | 486 ppm/4h                               |
| <b>Toluene (108-88-3)</b>   |  |
| LD50 Oral Rat   | 2600 mg/kg                               |
| LD50 Dermal Rabbit  | 12000 mg/kg                              |
| LC50 Inhalation Rat   | 25.7 mg/l/4h                             |

**Skin Corrosion/Irritation:** Causes skin irritation.

**Serious Eye Damage/Irritation:** Causes serious eye damage.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** May cause genetic defects.

**Carcinogenicity:** May cause cancer.

**Solvent naphtha, petroleum, medium aliphatic (64742-88-7)**

# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |   |
|--|---|
| <b>National Toxicology Program (NTP) Status</b>  | Evidence of Carcinogenicity.                  |
| <b>2-Butoxyethanol (111-76-2)</b>                |   |
| <b>IARC group</b>                                | 3   |
| <b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>  |   |
| <b>IARC group</b>                                | 3   |
| <b>Ethylbenzene (100-41-4)</b>                   |   |
| <b>IARC group</b>                                | 2B  |
| <b>National Toxicology Program (NTP) Status</b>  | Evidence of Carcinogenicity.                  |
| <b>OSHA Hazard Communication Carcinogen List</b> | In OSHA Hazard Communication Carcinogen list. |
| <b>2-Butoxyethanol (111-76-2)</b>                |   |
| <b>IARC group</b>                                | 3   |
| <b>Toluene (108-88-3)</b>                        |   |
| <b>IARC group</b>                                | 3   |
| <b>Polytetrafluoroethylene (9002-84-0)</b>       |   |
| <b>IARC group</b>                                | 3   |

**Reproductive Toxicity:** May damage fertility or the unborn child.

**Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness. May cause respiratory irritation.

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** Irritation of the respiratory tract and the other mucous membranes. High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

**Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis. This material is toxic in small amounts through skin contact, and can cause adverse health effects or death. This material may be absorbed through the skin and eyes. May cause an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva.

**Symptoms/Injuries After Ingestion:** This material is harmful orally and can cause adverse health effects or death in significant amounts. Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** May cause genetic defects. May cause cancer. May damage fertility or the unborn child.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General** : Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

|   |   |
|---|---|
| <b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>                                  |   |
| <b>LC50 Fish 1</b>  | 800 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])                      |
| <b>EC50 Daphnia 1</b>   | > 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)                                   |
| <b>2-Butoxyethanol (111-76-2)</b>   |   |
| <b>LC50 Fish 1</b>  | 1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])                     |
| <b>EC50 Daphnia 1</b>   | 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)                                    |
| <b>LC50 Fish 2</b>  | 2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)                              |
| <b>Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-, branched (127087-87-0)</b> |   |
| <b>LC50 Fish 1</b>  | 11.6 mg/l   |
| <b>Acetone (67-64-1)</b>  |   |
| <b>LC50 Fish 1</b>  | 4144.846 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)                          |
| <b>EC50 Daphnia 1</b>   | 1679.66 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])                        |
| <b>LC50 Fish 2</b>  | 6210 (6210 - 8120) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])       |
| <b>EC50 Daphnia 2</b>   | 12600 (12600 - 12700) mg/l (Exposure time: 48 h - Species: Daphnia magna)                   |
| <b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>  |   |
| <b>LC50 Fish 1</b>  | 7.19 (7.19 - 8.28) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| <b>EC50 Daphnia 1</b>   | 6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)                                    |
| <b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>   |   |
| <b>LC50 Fish 1</b>  | 3.3 mg/l  |

# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|   |  |
|---|--|
| EC50 Daphnia 1  | 3.82 mg/l (Exposure time: 48 h - Species: water flea)  |
| LC50 Fish 2   | 2.661 (2.661 - 4.093) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])       |
| NOEC Chronic Crustacea  | 1.17   |
| <b>Turpentine, oil (8006-64-2)</b>                              |  |
| LC50 Fish 1   | 29 mg/l (Exposure time: 96 h - Species: Danio rerio)   |
| EC50 Daphnia 1  | 6.4 (Exposure time: 48 h - Species: Daphnia magna)   |
| ErC50 (Algae)   | 17.1 mg/l (Exposure time 72 h - Species: Desmodesmus subspicatus)                              |
| <b>Solvent naphtha, petroleum, light aliphatic (64742-89-8)</b> |  |
| LC50 Fish 1   | >= 8.2 mg/l Exposure time 96 hour Species: Pimephales promelas                                 |
| NOEC Chronic Fish   | 14 day exposure Species: Pimephales promelas LC50: 5.2 mg/l                                    |
| <b>Ethylbenzene (100-41-4)</b>                                  |  |
| LC50 Fish 1   | 11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])                 |
| EC50 Daphnia 1  | 1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)                                  |
| LC50 Fish 2   | 4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])                    |
| NOEC Chronic Crustacea  | 0.956 mg/l   |
| <b>1-Methyl-2-pyrrolidone (872-50-4)</b>                        |  |
| LC50 Fish 1   | 832 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])                         |
| EC50 Daphnia 1  | 4897 mg/l (Exposure time: 48 h - Species: Daphnia magna)                                       |
| LC50 Fish 2   | 1072 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])                        |
| NOEC Chronic Crustacea  | 12.5 mg/l  |
| <b>2-Butoxyethanol (111-76-2)</b>                               |  |
| LC50 Fish 1   | 1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])                        |
| EC50 Daphnia 1  | 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)                                       |
| LC50 Fish 2   | 2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)                                 |
| <b>Toluene (108-88-3)</b>                                       |  |
| LC50 Fish 1   | 15.22 (15.22 - 19.05) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1  | 5.46 (5.46 - 9.83) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])                |
| LC50 Fish 2   | 12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])                        |
| EC50 Daphnia 2  | 11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)                                       |
| NOEC Chronic Fish   | 1.4 mg/l (Oncorhynchus kisutch)  |
| NOEC Chronic Crustacea  | 0.74 mg/l (Ceriodaphnia dubia)   |

### 12.2. Persistence and Degradability

|                                  |   |
|----------------------------------|---|
| <b>Ultimate 6K Fuel Enhancer</b> |   |
| Persistence and Degradability    | May cause long-term adverse effects in the environment. |
| <b>Acetone (67-64-1)</b>         |   |
| Persistence and Degradability    | Readily biodegradable in water.                         |

### 12.3. Bioaccumulative Potential

|  |                            |
|--|----------------------------|
| <b>Ultimate 6K Fuel Enhancer</b>                                 |                            |
| Bioaccumulative Potential  | Not established.           |
| <b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b> |                            |
| BCF Fish 1   | (bioaccumulation expected) |
| <b>2-Butoxyethanol (111-76-2)</b>                                |                            |
| Log Pow  | 0.81 (at 25 °C)            |
| <b>Acetone (67-64-1)</b>   |                            |
| BCF Fish 1   | 0.69                       |
| Log Pow  | -0.24                      |
| Log Kow  | -0.24                      |
| <b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>                       |                            |
| Log Pow  | 3.63                       |
| <b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>                  |                            |
| BCF Fish 1   | 0.6 (0.6 - 15)             |

# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                   |                  |
|-----------------------------------|------------------|
| Log Pow                           | 2.77 - 3.15      |
| Ethylbenzene (100-41-4)           |                  |
| BCF Fish 1                        | 15               |
| Log Pow                           | 3.2              |
| 1-Methyl-2-pyrrolidone (872-50-4) |                  |
| Log Pow                           | -0.46 (at 25 °C) |
| 2-Butoxyethanol (111-76-2)        |                  |
| Log Pow                           | 0.81 (at 25 °C)  |
| Toluene (108-88-3)                |                  |
| Log Pow                           | 2.7              |

### 12.4. Mobility in Soil

No additional information available

### 12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste Treatment Methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

**Additional Information:** Handle empty containers with care because residual vapors are flammable.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

Proper Shipping Name : FLAMMABLE LIQUIDS, TOXIC, N.O.S., (Solvent naphtha, petroleum, 2-Butoxyethanol)

Hazard Class : 3

Identification Number : UN1992

Label Codes : 3, 6.1

Packing Group : II

Marine Pollutant : Marine pollutant

ERG Number : 131



### 14.2. In Accordance with IMDG

Proper Shipping Name : FLAMMABLE LIQUIDS, TOXIC, N.O.S., (Solvent naphtha, petroleum, 2-Butoxyethanol)

Hazard Class : 3

Subsidiary Risk(s) : 6.1

Identification Number : UN1992

Packing Group : II

Label Codes : 3, 6.1

EmS-No. (Fire) : F-E

EmS-No. (Spillage) : S-D

Marine Pollutant : Marine pollutant



### 14.3. In Accordance with IATA

Proper Shipping Name : FLAMMABLE LIQUIDS, TOXIC, N.O.S., (Solvent naphtha, petroleum, 2-Butoxyethanol)

Packing Group : II

Identification Number : UN1992

Hazard Class : 3

Label Codes : 3, 6.1

Subsidiary Risk(s) : 6.1

ERG Code (IATA) : 3HP



## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

Ultimate 6K Fuel Enhancer

# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |   |
|--|---|
| <b>SARA Section 311/312 Hazard Classes</b>   | Physical hazard - Flammable (gases, aerosols, liquids, or solids)<br>Health hazard - Acute toxicity (any route of exposure)<br>Health hazard - Aspiration hazard<br>Health hazard - Carcinogenicity<br>Health hazard - Respiratory or skin sensitization<br>Health hazard - Germ cell mutagenicity<br>Health hazard - Reproductive toxicity<br>Health hazard - Serious eye damage or eye irritation<br>Health hazard - Skin corrosion or Irritation<br>Health hazard - Specific target organ toxicity (single or repeated exposure) |
| <b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>   |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |   |
| <b>2-Butoxyethanol (111-76-2)</b>  |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |   |
| <b>Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-, branched (127087-87-0)</b>  |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |   |
| <b>EPA TSCA Regulatory Flag</b>  | XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e., Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).  |
| <b>Acetone (67-64-1)</b>   |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |   |
| <b>CERCLA RQ</b>   | 5000 lb   |
| <b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>   |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory<br>Subject to reporting requirements of United States SARA Section 313 |   |
| <b>SARA Section 313 - Emission Reporting</b>   | 1 %   |
| <b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>  |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory<br>Subject to reporting requirements of United States SARA Section 313 |   |
| <b>CERCLA RQ</b>   | 100 lb  |
| <b>SARA Section 313 - Emission Reporting</b>   | 1 %   |
| <b>Turpentine, oil (8006-64-2)</b>   |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |   |
| <b>Solvent naphtha, petroleum, light aliphatic (64742-89-8)</b>  |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |   |
| <b>Ethylbenzene (100-41-4)</b>   |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory<br>Subject to reporting requirements of United States SARA Section 313 |   |
| <b>CERCLA RQ</b>   | 1000 lb   |
| <b>SARA Section 313 - Emission Reporting</b>   | 0.1 %   |
| <b>1-Methyl-2-pyrrolidone (872-50-4)</b>   |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory<br>Subject to reporting requirements of United States SARA Section 313 |   |
| <b>SARA Section 313 - Emission Reporting</b>   | 1 %   |
| <b>2-Butoxyethanol (111-76-2)</b>  |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |   |
| <b>Toluene (108-88-3)</b>  |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory<br>Subject to reporting requirements of United States SARA Section 313 |   |
| <b>CERCLA RQ</b>   | 1000 lb   |
| <b>SARA Section 313 - Emission Reporting</b>   | 1 %   |
| <b>Polytetrafluoroethylene (9002-84-0)</b>   |   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |   |

# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                 |  |
|---------------------------------|--|
| <b>EPA TSCA Regulatory Flag</b> | XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e., Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)). |
|---------------------------------|--|

### 15.2. US State Regulations

|  |   |
|--|---|
| <b>Ethylbenzene (100-41-4)</b>   |   |
| <b>U.S. - California - Proposition 65 - Carcinogens List</b>   | WARNING: This product contains chemicals known to the State of California to cause cancer.        |
| <b>1-Methyl-2-pyrrolidone (872-50-4)</b>   |   |
| <b>U.S. - California - Proposition 65 - Developmental Toxicity</b>   | WARNING: This product contains chemicals known to the State of California to cause birth defects. |
| <b>Toluene (108-88-3)</b>  |   |
| <b>U.S. - California - Proposition 65 - Developmental Toxicity</b>   | WARNING: This product contains chemicals known to the State of California to cause birth defects. |
| <b>2-Butoxyethanol (111-76-2)</b>  |   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List  |   |
| <b>Acetone (67-64-1)</b>   |   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) List |   |
| <b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>   |   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) List |   |
| <b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>  |   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) List |   |
| <b>Turpentine, oil (8006-64-2)</b>   |   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List  |   |
| <b>Ethylbenzene (100-41-4)</b>   |   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) List |   |
| <b>1-Methyl-2-pyrrolidone (872-50-4)</b>   |   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List  |   |
| <b>2-Butoxyethanol (111-76-2)</b>  |   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List  |   |
| <b>Toluene (108-88-3)</b>  |   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) List |   |
| <b>Polytetrafluoroethylene (9002-84-0)</b>   |   |

# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 11/13/2024  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

#### GHS Full Text Phrases:

|                                 |  |
|---------------------------------|--|
| Acute Tox. 3 (Dermal)           | Acute toxicity (dermal) Category 3                               |
| Acute Tox. 3 (Inhalation:vapor) | Acute toxicity (inhalation:vapor) Category 3                     |
| Acute Tox. 4 (Dermal)           | Acute toxicity (dermal) Category 4                               |
| Acute Tox. 4 (Inhalation:vapor) | Acute toxicity (inhalation:vapor) Category 4                     |
| Acute Tox. 4 (Oral)             | Acute toxicity (oral) Category 4                                 |
| Aquatic Acute 2                 | Hazardous to the aquatic environment - Acute Hazard Category 2   |
| Aquatic Acute 3                 | Hazardous to the aquatic environment - Acute Hazard Category 3   |
| Aquatic Chronic 2               | Hazardous to the aquatic environment - Chronic Hazard Category 2 |
| Aquatic Chronic 3               | Hazardous to the aquatic environment - Chronic Hazard Category 3 |
| Asp. Tox. 1                     | Aspiration hazard Category 1                                     |
| Carc. 1B                        | Carcinogenicity Category 1B                                      |
| Carc. 2                         | Carcinogenicity Category 2                                       |
| Comb. Dust                      | Combustible Dust   |
| Eye Dam. 1                      | Serious eye damage/eye irritation Category 1                     |
| Eye Irrit. 2A                   | Serious eye damage/eye irritation Category 2A                    |
| Eye Irrit. 2B                   | Serious eye damage/eye irritation Category 2B                    |
| Flam. Liq. 1                    | Flammable liquids Category 1                                     |
| Flam. Liq. 2                    | Flammable liquids Category 2                                     |
| Flam. Liq. 3                    | Flammable liquids Category 3                                     |
| Flam. Liq. 4                    | Flammable liquids Category 4                                     |
| Muta. 1B                        | Germ cell mutagenicity Category 1B                               |
| Repr. 1B                        | Reproductive toxicity Category 1B                                |
| Repr. 2                         | Reproductive toxicity Category 2                                 |
| Skin Irrit. 2                   | Skin corrosion/irritation Category 2                             |
| Skin Sens. 1                    | Skin sensitization, Category 1                                   |
| STOT RE 2                       | Specific target organ toxicity (repeated exposure) Category 2    |
| STOT SE 3                       | Specific target organ toxicity (single exposure) Category 3      |
| STOT SE 3                       | Specific target organ toxicity (single exposure) Category 3      |
| H224                            | Extremely flammable liquid and vapor                             |
| H225                            | Highly flammable liquid and vapor                                |
| H226                            | Flammable liquid and vapor                                       |
| H227                            | Combustible liquid   |
| H302                            | Harmful if swallowed   |
| H304                            | May be fatal if swallowed and enters airways                     |
| H311                            | Toxic in contact with skin                                       |
| H312                            | Harmful in contact with skin                                     |
| H315                            | Causes skin irritation   |
| H317                            | May cause an allergic skin reaction                              |
| H318                            | Causes serious eye damage  |
| H319                            | Causes serious eye irritation                                    |
| H320                            | Causes eye irritation  |
| H331                            | Toxic if inhaled   |
| H332                            | Harmful if inhaled   |
| H335                            | May cause respiratory irritation                                 |

# Ultimate 6K Fuel Enhancer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|      |   |
|------|---|
| H336 | May cause drowsiness or dizziness                                 |
| H340 | May cause genetic defects   |
| H350 | May cause cancer  |
| H351 | Suspected of causing cancer                                       |
| H360 | May damage fertility or the unborn child                          |
| H361 | Suspected of damaging fertility or the unborn child               |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H401 | Toxic to aquatic life   |
| H402 | Harmful to aquatic life   |
| H411 | Toxic to aquatic life with long lasting effects                   |
| H412 | Harmful to aquatic life with long lasting effects                 |

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

SDS US (GHS HazCom)